

RAVENOL ETC Hot Climate -15C Protect C12evo



1,5 l

Vendor:
1410167-150



5 l

Vendor:
1410167-005



20 l

Vendor:
1410167-020



20 l, ecobox

Vendor:
1410167-B20



60 l

Vendor:
1410167-060



208 l

Vendor:
1410167-208



1 000 l

Vendor:
1410167-700

Characteristics

Title	Value	Audit
ASTM	D3306, D4985, D6210	
Համապատասխանում է արտադրողի պահանջներին	BMW LC-87, BS 6580:2010 (GB), CUNA NC 956-16 (Italien), Cummins CES 14603, DTFR 29D100 (MB 326.0), Deutz DQC CC-14, Fiat 9.55523, Ford ESD-M97B49-A, IVECO 18-1830, JIS K 2234 (Japan), Liebherr LH-01-COL3A, MAN 324 Type NF, MAN 324 Type Si-OAT, MB 326.0, MB 326.6 (Premix), MTU MTL 5048, O Norm V 5123, SAE J 1034, Scania TB 1451, VOLVO TR 1286083, VOLVO TR-31854114-002, VOLVO VCS-2, VW TL 774-L (entspricht G12evo)	
Հատուկ հզորություն 20°C-ի դեպքում	1053 գ/սմ ³	EN ISO 12185
Գույն	Розовый	տեսողական
pH արժեքը 20 °C-ում	>8	ASTM D1287
Սառեցման կետ	0 °C	ASTM D1177